



VisiPatch® 360 to VisiPatch® 360 1 Pair Patch Cord, Dark Gray Jacket

## Product Classification

<b>Portfolio</b>	SYSTIMAX®
<b>Brand</b>	VisiPatch 360®   VisiPatch®
<b>Product Type</b>	Twisted pair patch cord
<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America   North America

## Dimensions

<b>Cord Length, maximum</b>	30 m   100 ft
<b>Cord Length, minimum</b>	1 m   1 ft

## Electrical Specifications

<b>ANSI/TIA Category</b>	5e
<b>dc Resistance, maximum</b>	0.30 ohm

## Environmental Specifications

<b>Environmental Space</b>	Non-plenum
<b>Flammability Rating</b>	UL 94 V-0
<b>Operating Temperature</b>	-10 °C to +60 °C (+14 °F to +140 °F)
<b>Safety Standard</b>	cETL   ETL

## General Specifications

<b>Cable Type</b>	U/UTP (unshielded)
<b>Interface, connector A</b>	VisiPatch® 360
<b>Interface, connector B</b>	VisiPatch® 360
<b>Jacket Color</b>	Dark gray
<b>Interface Feature, connector A</b>	Standard
<b>Interface Feature, connector B</b>	Standard
<b>Package Quantity</b>	1
<b>Pairs, quantity</b>	1

## Mechanical Specifications

<b>Conductor Type</b>	Stranded
<b>Contact Plating Material</b>	Precious metals
<b>Material Type</b>	Copper alloy   Polycarbonate
<b>Plug Insertion Life, minimum</b>	200 times
<b>Plug Retention Force, minimum</b>	18 N   4 lbf
<b>Wiring</b>	T568B

## Wiring Diagram

	Connector A	Connector B
Position 1	Blue	Blue
Position 2	Lt. Blue	Lt. Blue
Position 3		
Position 4		
Position 5		
Position 6		
Position 7		
Position 8		

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
RoHS 2011/65/EU	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



## Included Products

848202800 | 1074C DG 1/24 RVAR (Product Component—not orderable) — GigaSPEED XL® 1074C Category 5e U/UTP Cable, non-plenum, dark gray jacket, 1 pair count, variable length, reel