



SYSTIMAX 360™ GigaSPEED X10D® Evolve High Density Shielded Modular Panel, 24 port

Product Classification

Portfolio	SYSTIMAX®
Brand	GigaSPEED X10D®   SYSTIMAX 360™
Product Type	RJ45 patch panel
Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America

Dimensions

Depth, with cable management	165.10 mm   6.50 in
Height	43.69 mm   1.72 in
Weight	0.82 kg   1.80 lb
Width	482.60 mm   19.00 in

Electrical Specifications

ANSI/TIA Category	6A
Dielectric Withstand Voltage, RMS, contact-to-contact	1,000 Vac @ 60 Hz
Insulation Resistance, minimum	500 MOhm

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Relative Humidity	Up to 95%, non-condensing
Safety Standard	cUL   UL
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Intelligence Type	iPatch® ready
Total Ports, quantity	24
Cable Type	Shielded
Color	Cool gray   Satin chrome
Package Quantity	1
Rack Type	EIA 19 in

Rack Units1.0

Mechanical Specifications

Panel Style	Straight
Conductor Gauge, solid	22 AWG   24 AWG
Conductor Gauge, stranded	22 AWG   24 AWG
Conductor Type	Solid   Stranded
Contact Plating Material	Precious metals
Material Type	High-impact, flame retardant, thermoplastic   Powder-coated steel
Plug Insertion Life, minimum	750 times
Plug Insertion Life, test plug	IEC 60603-7 compliant plug
Plug Retention Force, minimum	30 lbf   133 N
Termination Contact Plating	Nickel
Termination Type	IDC
Wiring	T568A   T568B

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

