



SYSTIMAX 360™ GigaSPEED X10D® Evolve High Density Shielded Angled Modular Panel, 48 port

Product Classification

Portfolio

SYSTIMAX®

Brand

GigaSPEED X10D® | SYSTIMAX 360™

Product Type

RJ45 patch panel

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Dimensions

Depth, with cable management

266.70 mm | 10.50 in

Height

88.90 mm | 3.50 in

Weight

1.54 kg | 3.40 lb

Width

482.60 mm | 19.00 in

Electrical Specifications

ANSI/TIA Category

6A

Dielectric Withstand Voltage, RMS, contact-to-contact

1,000 Vac @ 60 Hz

Insulation Resistance, minimum

500 MOhm

Environmental Specifications

Flammability Rating

UL 94 V-0

Operating Temperature

-10 °C to +60 °C (+14 °F to +140 °F)

Relative Humidity

Up to 95%, non-condensing

Safety Standard

cUL | UL

Storage Temperature

-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Intelligence Type

iPatch® ready

Total Ports, quantity

48

Cable Type

Shielded

Color

Cool gray | Satin chrome

Package Quantity

1

Rack Type

EIA 19 in

Rack Units

2.0

Mechanical Specifications

Panel Style	Angled
Conductor Gauge, solid	22 AWG 24 AWG
Conductor Gauge, stranded	22 AWG 24 AWG
Conductor Type	Solid Stranded
Contact Plating Material	Precious metals
Material Type	High-impact, flame retardant, thermoplastic Powder-coated steel
Plug Insertion Life, minimum	750 times
Plug Insertion Life, test plug	IEC 60603-7 compliant plug
Plug Retention Force, minimum	30 lbf 133 N
Termination Contact Plating	Nickel
Termination Type	IDC
Wiring	T568A T568B

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

