760152561 | 360-IPR-1100-E-GS3-1U-24



SYSTIMAX 360™ GigaSPEED XL® 1100GS3 Evolve Category 6 U/UTP Patch Panel, 24 port

Product Classification

PortfolioSYSTIMAX®BrandGigaSPEED XL®Product TypeRJ45 patch panel

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North

America

Dimensions

 Depth, with cable management
 165.10 mm | 6.50 in

 Diameter Over Dielectric, maximum
 1.168 mm | 0.046 in

 Diameter Over Dielectric, minimum
 0.762 mm | 0.030 in

 Height
 44.45 mm | 1.75 in

 Weight
 0.86 kg | 1.90 lb

 Width
 482.60 mm | 19.00 in

Electrical Specifications

ANSI/TIA Category 6

Current Rating at Temperature 1.5 A @ 20 °C | 1.5 A @ 68 °F

Dielectric Withstand Voltage, RMS, conductive surface 1,500 Vac @ 60 Hz Dielectric Withstand Voltage, RMS, contact-to-contact 1,000 Vac @ 60 Hz

Insulation Resistance, minimum 500 MOhm

Environmental Specifications

Flammability Rating UL 94 V-0

Operating Temperature -10 °C to +60 °C (+14 °F to +140 °F)

Relative Humidity Up to 95%, non-condensing

Safety Standard CUL | UL

Storage Temperature $-40 \,^{\circ}\text{C}$ to $+70 \,^{\circ}\text{C}$ (-40 $^{\circ}\text{F}$ to $+158 \,^{\circ}\text{F}$)

General Specifications

Intelligence Type iPatch® ready

Total Ports, quantity 24

page 1 of 2 August 28, 2019



760152561 | 360-IPR-1100-E-GS3-1U-24

Cable Type Unshielded

Color Cool gray | Satin chrome

Modules, quantity 4
Package Quantity 1

Rack TypeEIA 19 inRack Units1.0

Mechanical Specifications

Panel Style Straight

Conductor Gauge, solid22 AWG | 24 AWGConductor Gauge, stranded22 AWG | 24 AWGConductor TypeSolid | StrandedContact Plating MaterialPrecious metals

Material Type High-impact, flame retardant, thermoplastic | Powder-coated steel

Plug Insertion Life, minimum 750 times

Plug Insertion Life, test plug IEC 60603-7 compliant plug

Plug Retention Force, minimum 30 lbf | 133 N

Termination Contact Plating Nickel
Termination Type IDC

Wiring T568A | T568B

Regulatory Compliance/Certifications

Agency Classification RoHS 2011/65/EU Compliant

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system





